

Single & Extension Ladders

Standard Features

1-1/4" OD slip-resistant serrated aluminum rungs.

Large aluminum swivel safety shoes with thick rubber treads may be used in either tread or spike down position for improved traction in many environments.

All components are field repairable which increases ladder life cycle and reduces costs.

IND-F: Single Fiberglass Ladders

MODEL	LENGTH	WIDTH	LBS.
IND-F-410-08	8'	19 1/16"	26
IND-F-410-10	10'	19 1/16"	33
IND-F-410-12	12'	19 1/16"	37
IND-F-410-14	14'	19 1/16"	44
IND-F-410-16	16'	19 1/16"	51
IND-F-410-18	18'	19 1/16"	58
IND-F-410-20	20'	19 1/16"	65

IND-F: Fiberglass Extension Ladders

- Oversized 2-1/4" pulley and 1/2" poly rope allow easy operation

MODEL	UNEXTEND.	EXTEND.	WIDTH	LBS.
IND-F-420-16	8'7"	13'7"	22 5/16"	65
IND-F-420-20	10'7"	17'7"	22 5/16"	76
IND-F-420-24	12'7"	21'7"	22 5/16"	90
IND-F-420-28	14'7"	25'7"	22 5/16"	101
IND-F-420-32	16'7"	29'7"	22 5/16"	118
IND-F-420-36	18'7"	33'7"	22 5/16"	135
IND-F-420-40	20'7"	37'7"	22 5/16"	142

IND-A: Single Aluminum Ladders

MODEL	LENGTH	WIDTH	LBS.
IND-A-010-08	8'	19 1/16"	22
IND-A-010-10	10'	19 1/16"	28
IND-A-010-12	12'	19 1/16"	34
IND-A-010-14	14'	19 1/16"	41
IND-A-010-16	16'	19 1/16"	47
IND-A-010-18	18'	19 1/16"	53
IND-A-010-20	20'	19 1/16"	60

IND-A: Aluminum Extension Ladders

- Oversized 2-1/4" pulley and 1/2" poly rope allow easy operation

MODEL	UNEXTEND.	EXTEND.	WIDTH	LBS.
IND-A-020-16	8'5"	13'5"	22 1/4"	58
IND-A-020-20	10'5"	17'5"	22 1/4"	70
IND-A-020-24	12'5"	21'5"	22 1/4"	92
IND-A-020-28	14'5"	25'5"	22 1/4"	105
IND-A-020-32	16'5"	29'5"	22 1/4"	120
IND-A-020-36	18'5"	33'5"	22 1/4"	128
IND-A-020-40	20'5"	37'5"	22 1/4"	144

DLLH-S: Single Aluminum Ladders

MODEL	LENGTH	WIDTH	LBS.
DLLH-S-06	6'	20"	9
DLLH-S-08	8'	20"	12
DLLH-S-10	10'	20"	15
DLLH-S-12	12'	20"	18
DLLH-S-14	14'	20"	21
DLLH-S-16	16'	20"	24
DLLH-S-18	18'	20"	27
DLLH-S-20	20'	20"	30

DLLH-E: Aluminum Extension Ladders

- Oversized 2-1/4" pulley and 1/2" poly rope allow easy operation

MODEL	SECTION LENGTH	UNEXT. LENGTH	MAX. CLIMB LENGTH	WIDTH	LBS.
DLLH-E-16	16'	8'	13'	20"	28
DLLH-E-20	20'	10'	17'	20"	33
DLLH-E-24	24'	12'	21'	20"	38
DLLH-E-28	28'	14'	25'	20"	47
DLLH-E-32	32'	16'	29'	20"	52
DLLH-E-36	36'	18'	32'	20"	59
DLLH-E-40	40'	20'	35'	20"	64

500 lb. Capacity Fiberglass Single/Extension Ladders IND Series



Single & Extension Ladders

**500 lb. Capacity Aluminum
Single/Extension Ladders**
IND Series



**300 lb. Capacity Aluminum
Single/Extension Ladders**
DLLH Series



The 500 lb. duty rated fiberglass and aluminum IND series exceed all OSHA requirements as we interpret them.

The DLLH series is Type 1A, 300 lb. duty rated. Meets and/or exceeds ANSI and OSHA requirements as we interpret them.