

Specialty Ladders

Extra Heavy-Duty Shelf Ladders

- 1-1/2" wide angle aluminum feet with rubber treads.
- 4" deep slip-resistant ribbed steps.
- Tool holes in top cap for added convenience.
- All parts replaceable; ladders can be repaired at your facility.
- Each step braced front and back - 4 gussets and 16 rivets per step.
- Tapered for increased stability.
- Special padded tops for use against tank sides optional.
- Type 1A, 300 lb. duty rating.



Aluminum

| MODEL | HEIGHT | BOTTOM WIDTH | LBS. |
|----------|--------|--------------|------|
| S100H-03 | 3' | 21" | 10 |
| S100H-04 | 4' | 22" | 11 |
| S100H-05 | 5' | 24" | 13 |
| S100H-06 | 6' | 25" | 14 |
| S100H-07 | 7' | 26" | 18 |
| S100H-08 | 8' | 28" | 22 |
| S100H-09 | 9' | 29" | 24 |
| S100H-10 | 10' | 31" | 28 |
| S100H-11 | 11' | 32" | 30 |
| S100H-12 | 12' | 33" | 34 |
| S100H-13 | 13' | 35" | 37 |
| S100H-14 | 14' | 36" | 40 |
| S100H-15 | 15' | 38" | 43 |
| S100H-16 | 16' | 39" | 48 |
| S100H-17 | 17' | 41" | 51 |
| S100H-18 | 18' | 42" | 54 |
| S100H-19 | 19' | 43" | 60 |
| S100H-20 | 20' | 45" | 63 |

Fiberglass

| MODEL | HEIGHT | BOTTOM WIDTH | LBS. |
|-----------|--------|--------------|------|
| PS100H-03 | 3' | 21" | 11 |
| PS100H-04 | 4' | 22" | 13 |
| PS100H-05 | 5' | 24" | 15 |
| PS100H-06 | 6' | 25" | 17 |
| PS100H-07 | 7' | 26" | 21 |
| PS100H-08 | 8' | 28" | 24 |
| PS100H-09 | 9' | 29" | 28 |
| PS100H-10 | 10' | 31" | 31 |
| PS100H-11 | 11' | 32" | 35 |
| PS100H-12 | 12' | 34" | 40 |
| PS100H-14 | 14' | 36" | 48 |
| PS100H-16 | 16' | 39" | 56 |

Security Access Ladders

- Locking device secures the ladder from unauthorized use.
- Opens to 12-1/2" wide when in use, and stores to only 2-1/2" wide in the closed, locked position.
- All aluminum construction facilitates use either indoors or out without worry of corrosion.
- Available with top (TP) or bottom (BP) locking device. Please specify when ordering. Padlock not included.

| MODEL | OPEN LENGTH | HEIGHT TO TOP RUNG | LBS. |
|--------|-------------|--------------------|------|
| SAL-08 | 8' 11" | 6' 10" | 12 |
| SAL-10 | 11' 2" | 10' 0" | 14 |
| SAL-12 | 13' 4" | 11' 3" | 17 |
| SAL-14 | 15' 7" | 13' 6" | 21 |
| SAL-16 | 17' 10" | 15' 9" | 25 |
| SAL-24 | 25' 8" | 23' 8" | 26 |



Specialty Ladders

Tank Inspection Ladders

- Designed for internal tank inspection and cleaning.
- Aluminum construction with replaceable 1-1/4" serrated rungs.
- 12" wide (13-5/8" over shoes) to facilitate entry into tank cars through narrow access hatches.
- Swivel safety shoes standard.
- Type 1A, 300 lb. duty rating.



| MODEL | LENGTH | WIDTH | LBS. |
|--------|--------|-------|------|
| TIL-08 | 8' | 12" | 12 |
| TIL-10 | 10' | 12" | 15 |
| TIL-12 | 12' | 12" | 18 |
| TIL-14 | 14' | 12" | 21 |
| TIL-16 | 16' | 12" | 24 |
| TIL-18 | 18' | 12" | 27 |
| TIL-20 | 20' | 12" | 30 |

Folding Inspection Ladders

- Designed for use in closed-in areas with extremely narrow access routes; i.e., inside storage tanks, manholes, water treatment plants, etc.
- Folds to 5-1/4" for easy maneuverability.
- Aluminum marine grade alloy construction.
- Safety shoes standard.
- Type 1A, 300 lb. duty rating.



| MODEL | LENGTH | | WIDTH | | LBS. |
|--------|--------|--------|---------|--------|------|
| | OPEN | CLOSED | OPEN | CLOSED | |
| FIL-08 | 8' | 8'11" | 15 1/2" | 5 1/4" | 14 |
| FIL-10 | 10' | 11'2" | 15 1/2" | 5 1/4" | 16 |
| FIL-12 | 12' | 13'4" | 15 1/2" | 5 1/4" | 19 |
| FIL-14 | 14' | 15'7" | 15 1/2" | 5 1/4" | 23 |

Max Stack Ladders

- Sections can be combined to produce the desired length; ladder must be laterally supported every 30'.
- All aluminum construction reduces weight and resists corrosion.
- Each ladder section has a male and a female end to enable easy connection utilizing wing nuts and thumb screws.
- 16" wide to facilitate ease of handling and access through hatches and manholes.
- Bottom section requires heavy-duty aluminum swivel safety shoes with thick rubber tread for added slip-resistance.

| MODEL | LENGTH | WIDTH | LBS. |
|--------|--------|-------|------|
| MAX-03 | 3' | 16" | 14 |
| MAX-04 | 4' | 16" | 17 |
| MAX-05 | 5' | 16" | 20 |
| MAX-06 | 6' | 16" | 23 |
| MAX-07 | 7' | 16" | 26 |
| MAX-08 | 8' | 16" | 29 |
| MAX-09 | 9' | 16" | 32 |
| MAX-10 | 10' | 16" | 35 |
| MAX-12 | 12' | 16" | 41 |

